

new

USMOWER

EX30

EXCAVATOR FLAIL MOWER



Optional thumb saddle and ground roller available.



Parent Machine Specific Mount Included in Price



Built for parent machines from 4000-10000 lbs

- Cuts and mulches up to 4" trees, shrubs, vegetation, grass and weeds.
- Used for clearing riverbanks, ditches, hillsides, utility right of ways, walking trails and more
- Triple Blade Configuration-2 flail blades (2lb)/1 thatch blade (2lb)
- 5" x 3/8" Wall DOM electronically balanced cutter shaft
- 3000PSI Pressure & Return hoses with 1/2" flat face couplers
- 1/4" x 98" case drain line with 3/8" flat face coupler
- 100's of mount configurations available or will build to suit-**INCLUDED**
- Parker Hydraulic Gear Motor matched to available auxiliary oil flow
- Domestic High Strength Steel-3mm shroud, 3/16" end plates, 3/8" bearing plates
- AR400 Skid Shoes Placed for Ultimate Drag Reduction
- Polyester powder coat high visibility yellow finish with UV Protection
- Adaptable to hydraulics location on Parent Machine
- 12 Month Warranty parts & labor



Specifications

- Cutting Width-30"
- Cutting Capacity-4"
- Required auxiliary flow 8-22gpm
- Approximate Weight 550lbs

Manufactured in the USA

www.usmower.com