

USMOWER

Product Reference

Quality Since 1999



11949 Westar Ln
Burlington, WA 98233
360.757.7555

www.usmower.com

Flail Mowing Attachments

U.S. Mower Flail attachments are best suited to general brush cutting for materials including grass, brambles, shrubs & trees up to 3-4" in diameter. Smaller, uniform chips distribute evenly across the cut path. This cut material typically acts as a light mulch that easily breaks down in contact with soil.



EX30-2020



EX30HD-2020



EX40

Approx. Attachment Weight (with mount)	550 lbs.	610 lbs.	950 lbs.
Parent Machine Weight Requirements	4500-10000 lbs.	9000-14000 lbs.	10000-18000 lbs.
Cutting Width	30"	30"	40"
Cutting Capacity	4"	4"	4"
Required Auxiliary Flow	8-22 gpm	8-22 gpm	15-40 gpm
Thumb Saddle Option	Yes	Yes	Yes
Roller Option	Yes	Yes	Yes
Piston Motor Option	No	No	Yes
BDRV Option*	Yes	Yes	Yes



EX40HD



EX50HDBD



EX60HDBD

Approx. Attachment Weight (with mount)	1150 lbs.	1800 lbs.	1950 lbs.
Parent Machine Weight Requirements	16000-25000 lbs.	22000-35000 lbs.	30000-50000 lbs.
Cutting Width	40"	50"	60"
Cutting Capacity	4"	4-6"	4-6"
Required Auxiliary Flow	15-40 gpm	25-50 gpm	30-55 gpm
Thumb Saddle Option	Yes	Yes	Yes
Roller Option	Yes	No	No
Piston Motor Option	Yes	Yes	Yes
BDRV Option*	Yes	Yes	Yes

*BDRV option available for 2021 models now available. Please consult with sales to determine best option for your attachment and application.

Rotary Mowing Attachments

Rotary Mowers operate by blades attached to a rotating bar or disc horizontally when the head is in contact with the ground. These operate in the toughest conditions. Ideal for forestry work, fire breaks, rural or remote roadsides and reclamation clearing.



EX50HDR



EX60HDR



EX60SHDR

	EX50HDR	EX60HDR	EX60SHDR
Approx. Attachment Weight (with mount)	1600 lbs.	1700 lbs.	1600-2700 lbs.
Parent Machine Weight Requirements	18000-28000 lbs.	28000-40000 lbs.	35000-55000 lbs.
Cutting Width	50"	60"	60"
Cutting Capacity	8"	8"	8"
Required Auxiliary Flow	16-55 gpm	20-55 gpm	35-55 gpm
Thumb Saddle Option	Yes	Yes	Yes
Gate Options	Multiple, Chains, Mechanical Functions	Multiple, Chains, Mechanical Functions	Multiple, Chains, Mechanical Functions
Piston Motor Option	Yes	Yes	Yes
Bi-Directional Function	Yes	Yes	Yes
Relief Valve (BDRV)*	Yes	Yes	Yes
Blade Size	12 lbs.	12 lb. (23 lb. Option)	23 lb.

www.usmower.com

360.757.7555

Skid Steers



Rotary

	QA60	QA72
Approx. Attachment Weight	1450 lbs.	2050 lbs.
Parent Machine Weight Requirements	6000 lbs. +	9500 lbs. +
Cutting Width	60"	72"
Cutting Capacity	8	10"
Required Auxiliary Flow	20-45 gpm	30-45 gpm
Piston Motor Option	Yes	Yes
Bi-Directional Function Relief Valve (BDRV)*	Yes	Yes
Blade Size	21 lb. (23 lb. Option)	27 lb.



Flail

	RZ60HD	RZ72HD	RZ84HD
Approx. Attachment Weight	1625 lbs.	1875 lbs.	2200 lbs.
Parent Machine Weight Requirements	5000 lbs. +	6000 lbs. +	7000 lbs. +
Cutting Width	60"	72"	84"
Cutting Capacity	6"	6"	6"
Required Auxiliary Flow	30-55 gpm	30-55 gpm	25-40 gpm
Piston Motor Option	Yes	Yes	Yes
Bi-Directional Function Relief Valve (BDRV)**	Yes	Yes	Yes

**Required on Piston Motor Upgrades

Parts & Services

U.S. Mower Aims to Keep You Mowing with Parts on Demand & Services.

Blades, Kits & More

- EX30 to EX60HDBD - Flail Blade Kits - Blades, Bolts, Nuts & Pins In-Stock
- 12 & 23 lb. Rotary Blade Kits - Blades, Bolts, Nuts & Pins In-Stock
- Pin-Punch Tool
- Bearings
- Iso-rings/Torque Discs
- Complete Shaft-Builds(EX30 through EX40HD In-Stock)
- Deflector Shields & Clamp Strips
- Replacement Gear & Piston Motors
- Grease-Line Push-On Conversion Kits
- Replacement Mounts (fabrication may be required)
- Replacement Hoses & Fittings
- Drive-Shaft Nuts & Spanner Tools
- Thumb Saddles & Roller Kits
- Physical manuals provided; digital manuals available on request



EX30HD Shown with Thumb Saddle & Roller

Services

- Evaluate & repair wear and tear or damaged parts (see Warranty for US Mower coverage).
- Attachment re-configuration for new machines with different performance requirements.
- Live-person or email expert technician support.
- Same-day UPS Ground shipping on parts/exchanges for in-stock items.
- Multi-Unit Discounts & Group Shipping Deals.

Warranty

All U.S. Mower attachments are built with 100,000 psi yield strength steel construction and domestically manufactured machined parts. Blades & blade bolts meet stringent mechanical & physical properties and each mower has a high visibility yellow polyester powder coat finish with UV protection. Every detail is built with quality & performance for the end user in mind.

With that quality, U.S. Mower provides a 12-month Factory Warranty on all new attachments. Warranty coverage includes defects in workmanship and materials, which starts at the date of invoice to the end user. Valid for 12 months. See Full Warranty for Details.

www.usmower.com

360.757.7555

US MOWER



11949 Westar Ln
Burlington, WA 98233
360.757.7555

www.usmower.com